

# LGMT 2

## SKF general purpose industrial and automotive bearing grease

LGMT 2 is mineral oil based lithium soap thickened grease with excellent thermal stability within its operating temperature range. This premium quality, general purposes grease is suitable for a wide range of industrial and automotive applications.

- Excellent oxidation stability
- Good mechanical stability
- Excellent water resistance and rust inhibiting properties

### Typical applications:

- Agricultural equipment
- Automotive wheel bearings
- Conveyors
- Small electric motors
- Industrial fans

### Bearing operating conditions

Temperature	Medium
Speed	Medium
Load	Low to Medium
Vertical shaft	○
Fast outer ring rotation	—
Oscillating movements	—
Severe vibrations	+
Shock load or frequent start-up	—
Low noise	—
Low friction	○
Rust inhibiting properties	+
+ = Recommended    ○ = Suitable    — = Not suitable	

### Available pack sizes LGMT 2

	35 g tube	200 g tube
420 ml cartridge	1 kg can	5 kg can
18 kg can	50 kg drum	180 kg drum



Re-lubrication



## Technical data

<b>Designations</b>	<b>LGMT 2</b>		
<b>DIN 51825 code</b>	K2K-30	<b>Water resistance</b>	
<b>NLGI consistency class</b>	2	DIN 51 807/1, 3 hrs at 90 °C	1 max.
<b>Soap type</b>	Lithium	<b>Oil separation</b>	
<b>Colour</b>	Red brown	DIN 51 817, 7 days at 40 °C, static, %	1 - 6
<b>Base oil type</b>	Mineral	<b>Lubrication ability</b>	
<b>Operating temperature range, °C (°F)</b>	-30 to 120 (-22 to 250)	SKF R2F, running test B at 120 °C	Pass
<b>Dropping point DIN ISO 2176, °C (°F)</b>	180 min. (356 min.)	<b>Copper corrosion</b>	
<b>Base oil viscosity:</b>		DIN 51 811, 110 °C	2 max. (130 °C / 266 °F)
40 °C, mm <sup>2</sup> /s	110	<b>Rolling bearing grease life</b>	
100 °C, mm <sup>2</sup> /s	11	SKF R0F test L50 life at 10 000 rpm, hrs	-
<b>Penetration DIN ISO 2137:</b>		<b>EP performance</b>	
60 strokes, 10 <sup>-1</sup> mm	265 - 295	Wear scar DIN 51350/5, 1 400 N, mm	-
100 000 strokes, 10 <sup>-1</sup> mm	+50 max. (325 max.)	4-ball test, welding load DIN 51350/4	-
<b>Mechanical stability:</b>		<b>Fretting corrosion</b>	
Roll stability, 50 hrs at 80 °C, 10 <sup>-1</sup> mm	+ 50 max.	ASTM D4170 (mg)	-
SKF V2F test	'M'	<b>Designation</b>	<b>LGMT 2/(pack size)</b>
<b>Corrosion protection: SKF Emcor:</b>		* <i>Typical value</i>	
- standard ISO 11007	0 - 0		
- water washout test	0 - 0		
- salt water test (100% seawater)	0 - 1*		

© SKF is a registered trademark of the SKF Group  
© SKF Group 2009

The contents of this publication are the copyright of the publisher and may not be reproduced (even extracts) unless prior written permission is granted. Every care has been taken to ensure the accuracy of the information contained in this publication but no liability can be accepted for any loss or damage whether direct, indirect or consequential arising out of the use of the information contained herein.

MP/PDS LGMT2 EN • October 2009

[www.mapro.skf.com](http://www.mapro.skf.com) • [skf.com/lubrication](http://skf.com/lubrication)

